

TI GB 1886-F

20V Battery driven grease gun

For intensive use in challenging environments

The TLGB 1886-E battery driven grease gun offers the key features you need for tough jobs. The versatility of the two-speed design enables you to address all lubrication points with a single tool, protecting your equipment from costly repair and downtime. The tool's high-ratio gearing will move large quantities of grease guickly when needed, while its low gearing supports deliveries of up to 700 bar.

Thanks to its ergonomic rugged design, high-performance motor positioning and efficient handling, the TLGB 1886-E has been designed to withstand the intensive use found in demanding industries such as agriculture, construction, automotive, trucking, heavy equipment and wind energy.

- High performance for intensive use
- Built-in LED illuminates the work area
- LED indicators identify loss of prime, empty cartridge or blocked fittings
- Trapped air inside of the grease gun can be easily removed with the vent valve to restore priming
- High-pressure hose with protective antikink spring guards on each end
- Heavy-duty composite body with protective rubber overmold
- Easily and cleanly filled from drums with filler pumps
- Battery charge LED indicator



® SKF and Lincoln are registered trademarks of the SKF Group.

© SKF Group 2024

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information



Technical data

Designation

Grease output

Low speed setting High speed setting Maximum operating pressure Maximum peak pressure

Cartridges per battery charge

Length of hose Battery type Battery output Battery capacity

Voltage charger, V/Hz Carrying case dimensions

Weight (incl. battery) Total weight (incl. case)

Accessories

TLGB 21-2 TLGB 21-9 **TLGB 1875A** TI GB 21-1

TLGB 20-3

100 ml/min (3.5 oz/min) at 70 bar pressure 284 ml/min (10 oz/min) at 70 bar pressure

550 bar (8 000 psi) 700 bar (10 000 psi)

8.6 cartridges (200 bar counter pressure, low speed)

18 cartridges (free flow) 1220 mm (48 in)

Li-lon 20 V 2 500 mAh

200-240 V/ 50-60 Hz

650×140×393 mm (25.6×5.5×15.5 in)

3.4 kg (7.5 lb) 7.9 kg (17.4 lb)

20 V 2.5 Ah Li-lon battery 20 V 4.0 Ah Li-Ion battery

12/24V Battery charger for 12/20V (Li-lon) grease guns

Shoulder strap

High pressure hose 900 mm (36 in)

